


LED PANEL LIGHT - 2x2

Features Designed to fit any ceiling surface. Built-in for squared/rectangular ceilings with 2" or less installation depth. Suspended and hanging for other types of ceilings. Environmentally friendly and recyclable. Easy low cost maintenance and repair. UL, CUL, certified to wet location, DCL Listed.

Applications Art galleries, museums, homes, schools, offices, hotels, restaurants, retail stores, and other commercial and industrial applications.



Panel 2x2 40W 5200Lm Spec

| | |
|---------------------------|---------------------|
| 40W | rated power |
| ↑ 75% | wattage saved |
| AC100~277V | input-voltage |
| >0.9 | power factor |
| 50/60Hz | frequency |
| 5200Lm | lumens |
| 4000K/5000K | color temperature |
| >80 | CRI |
| THD: <20% (at 480V) | THD |
| 113° | beam angle |
| damp location | IP rating |
| frosted | lens |
| aluminum alloy + PC shell | materials |
| external | power |
| 50,000 hours | LED emitter life |
| yes | dimmable |
| 5 years | warranty |
| 23.7 x 23.7 x 1.9 | size (in) |
| 10.6 lbs | weight |
| -4°F to 122°F | working environment |
| >90% | power efficiency |

IGTLED
Lighting

model number IGTPL-0504040FD-2x2
IGTPL-0504050FD-2x2

