

# LED HIGH BAY LIGHT - 100W High Voltage

**Features** Ultra thin round disc design. Easy installation and maintenance. System light efficacy 140 LPW. Fin-type radiator technology. Mean Well HBG driver. Nichia 3030. Healthy ray, no UV or IR radiation. Friendly environment and energy saving. DLC, UL, cUL, SAA CE, RoHS approved. Five years warranty.

**Applications** Warehouse/manufacturing facilities. Industrial workshops. Golf courses. Convention centers/sporting arenas. Big-box retail stores. Cold storage facilities. Gymnasiums.



## High Bay High Voltage Light 100W 5000K Spec

|   |                     |
|---|---------------------|
| 100W  | rated power         |
| ↑ 75%   | wattage saved       |
| AC180-528V                                    | input-voltage       |
| >0.95   | power factor        |
| 50~60Hz                                       | frequency           |
| 140Lm   | lumens per watt     |
| 14000Lm                                       | lumens              |
| 5000K   | color temperature   |
| >75   | CRI                 |
| IP67  | IP rating           |
| 120°  | beam angle          |
| hook / chain mount, universal hanging bracket | base type           |
| clear   | lens                |
| polycarbonate                                 | material            |
| 18.1 x 18.1 x 7.1                             | size (in)           |
| 12.1  | weight (lbs)        |
| no  | dimmable            |
| 5 years                                       | warranty            |
| -22°F to 122°F                                | working environment |
| 50,000 hours                                  | LED emitter life    |
| 90%   | power efficiency    |

**IGT**LED  
Lighting

model number IGT HB-0210050C-HV

